

## **4K HDMI EDID Emulator** VC081

The VC081 4K HDMI EDID Emulator is designed to overcome EDID related problems which can occur when used with AV or KVM extenders, switches, and splitters. By learning the EDID from the HDMI display and relaying it to the video source, the VC081 can effectively resolve video communication problems that occur when EDID data between the HDMI video source and display are not correctly synchronized. Moreover, after the display's EDID is learned, the VC081 can be used in place of a monitor to keep a PC or Server awake for remote access via IP.

For product application, the VC081 is an ideal tool for wiring installation in traffic stations and commercial centers.













## Features

- Manages EDID communication between connected devices
- Effectively learn the EDID from the HDMI display and relay it to the video source
- HDMI 2.0 (3D, Deep Color, 4K); HDCP 2.2 compliant
- Superior video quality up to True 4K (3840 x 2160 @ 60Hz 4:4:4)
- LED indicators to show device status
- Powered by HDMI source
- Compact and lightweight design







## Specifications

_	
Function	VC081
Video Input	
Interfaces	1 x HDMI Type A Male (Black)
Impedance	100 Ώ
Video Output	
Interfaces	1 x HDMI Type A Female (Black)
Impedance	100 Ώ
Video	
Compliance	HDMI 2.0 (3D, Deep Color) HDCP 2.2 Compatible Consumer Electronic Control (CEC)
EDID Settings	EDID Mode: Default / Learning
Connectors	
Power	Bus-powered (5 VDC from source device)
LEDs	
Power	Power status (Green x 1)
Status	Learning (Blue x 1)
Power Consumption	DC5V: 0.25W
Environmental	
Operating Temperature	0 - 50 °C
Storage Temperature	-20 - 60 °C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Plastic (ABS)
Weight	0.1 kg
Dimensions (L x W x H)	4.40 x 1.18 x 2.40 cm

Product information is subject to change without prior notice.

Publish Date: 12/2018 V1.0

