

Specifications

Model			QB43C	QB50C	QB55C	QB65C	QB75C	QB85C
Display Panel	Diagonal Size	Class	43	50	55	65	75	85
		Measured	42.5	48.5	54.6	64.5	74.5	84.5
	Resolution		3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)	3,840 x 2,160 (16:9)
	Brightness (Typ.)		350 nit	350 nit	350 nit	350 nit	350 nit	350 nit
	Orientation		Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait
	Haze		2%	3%	2%	2%	5%	5%
	Contrast Ratio (Typ.)		4,000:1	4,000:1	4,000:1	4,000:1	4,000:1	4,000:1
	Type		VA	VA	VA	VA	VA	VA
	Active Display Area		941.184 (H) x 529.416 (V)	1,095.84 (H) x 616.41 (V)	1,209.6 (H) x 680.4 (V)	1,428.48 (H) x 803.52 (V)	1,650.24 (H) x 928.26 (V)	1,872.0 (H) x 1053.01 (V)
	Connectivity / Sound	Input	Pixel Pitch (mm)	0.245 x 0.245	0.285 x 0.285	0.315 x 0.315	0.372 x 0.372	0.429 x 0.429
Color Gamut			NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%	NTSC 72%
Operation Hour			16/7	16/7	16/7	16/7	16/7	16/7
Video			HDMI 2.0 (3)	HDMI 2.0 (3)	HDMI 2.0 (3)	HDMI 2.0 (3)	HDMI 2.0 (3)	HDMI 2.0 (3)
Output		Audio	N/A	N/A	N/A	N/A	N/A	N/A
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
		Tuner	N/A	N/A	N/A	N/A	N/A	N/A
		Video	N/A	N/A	N/A	N/A	N/A	N/A
Stereo		Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack	
WiFi / BT		N/A	N/A	N/A	N/A	N/A	N/A	
Mechanical Spec	External Control		O/O	O/O	O/O	O/O	O/O	O / O
	Speaker		RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45
	Dimension (mm)	10W 2ch	10W 2ch	10W 2ch	10W 2ch	10W 2ch	10W 2ch	10W 2ch
		Set	969.5 x 557.8 x 28.5	1,124.1 x 644.8 x 28.5	1,237.9 x 708.8 x 28.5	1,456.8 x 831.9 x 28.5	1,682.3 x 960.4 x 28.5	1,904.3 x 1,085.3 x 28.5
	Weight (kg)	Package	TBD	TBD	TBD	TBD	TBD	TBD
		Set	1,093 x 667 x 126	1,246 x 761 x 131	1,403 x 835 x 148	TBD	TBD	TBD
	VESA Mount		Package	TBD	TBD	TBD	TBD	TBD
	VESA Mount Screw (Min~Max)		200 x 200	200 x 200	200 x 200	400 x 300	400 x 400	400 x 400
	Bezel Width (mm)		M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	M8, 12~14mm	M8, 12~14mm
			11.5 (Even)	11.5 (Even)	11.5 (Even)	11.5 (Even)	13.4 (Even)	13.9 (Even)
Features	Key		UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0	UHD Signage with Built-in MagicInfoS10, SSSP10.0
	Internal Player	Operating System	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0	Tizen 7.0
		Processor	CA531.3GHz Quad-Core	CA531.3GHz Quad-Core	CA531.3GHz Quad-Core	CA531.3GHz Quad-Core	CA531.3GHz Quad-Core	CA531.3GHz Quad-Core
	H/W	Storage (FDM)	8GB (3GB available)	8GB (3GB available)	8GB (3GB available)	8GB (3GB available)	8GB (3GB available)	8GB (3GB available)
		2nd Gen. B2B Design	2nd Gen. B2B Design	2nd Gen. B2B Design	2nd Gen. B2B Design	2nd Gen. B2B Design	2nd Gen. B2B Design	2nd Gen. B2B Design
	Special	Center IR	Center IR	Center IR	Center IR	Center IR	Center IR	Center IR
		Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor	Temperature Sensor
		Ambient Sensor	Ambient Sensor	Ambient Sensor	Ambient Sensor	Ambient Sensor	Ambient Sensor	Ambient Sensor
		Auto Level	Auto Level	Auto Level	Auto Level	Auto Level	Auto Level	Auto Level
	Wi-Fi (2.4/5.0GHz dual) & BT		Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT	Wi-Fi (2.4/5.0GHz dual) & BT
Certification	Safety	Signage New Home Workspace	Signage New Home Workspace	Signage New Home Workspace	Signage New Home Workspace	Signage New Home Workspace	Signage New Home Workspace	Signage New Home Workspace
		(Microsoft365/VMWare/RDP)	(Microsoft365/VMWare/RDP)	(Microsoft365/VMWare/RDP)	(Microsoft365/VMWare/RDP)	(Microsoft365/VMWare/RDP)	(Microsoft365/VMWare/RDP)	(Microsoft365/VMWare/RDP)
	EMC	Custom Home	Custom Home	Custom Home	Custom Home	Custom Home	Custom Home	Custom Home
		Auto Source	Auto Source	Auto Source	Auto Source	Auto Source	Auto Source	Auto Source
	Environment	Switching & Recovery	Switching & Recovery	Switching & Recovery	Switching & Recovery	Switching & Recovery	Switching & Recovery	Switching & Recovery
		Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode	Dicom Simulation Mode
	IP Rating	Director Mode	Director Mode	Director Mode	Director Mode	Director Mode	Director Mode	Director Mode
		Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine	Upgradable Web-Engine
	Security	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform	Tizen Enterprise Platform
		Video Conference Solution	Video Conference Solution	Video Conference Solution	Video Conference Solution	Video Conference Solution	Video Conference Solution	Video Conference Solution
Power	Smart Calibration (Basic)		Smart Calibration (Basic)	Smart Calibration (Basic)	Smart Calibration (Basic)	Smart Calibration (Basic)	Smart Calibration (Basic)	Smart Calibration (Basic)
	Safety	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1	60950-1/62368-1
	EMC	Class B	Class B	Class B	Class B	Class B	Class A	Class A
	Environment	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT	ENERGY STAR 8.0, EPEAT
Power	IP Rating	IP5x	IP5x	IP5x	IP5x	IP5x	IP5x	IP5x
		Security	802.1 x (WPA2 Enterprise)	802.1 x (WPA2 Enterprise)	802.1 x (WPA2 Enterprise)	802.1 x (WPA2 Enterprise)	802.1 x (WPA2 Enterprise)	802.1 x (WPA2 Enterprise)
	PowerSupply	: EAP-TLS, EAP-TTLS, EAP-PEAP	: EAP-TLS, EAP-TTLS, EAP-PEAP	: EAP-TLS, EAP-TTLS, EAP-PEAP	: EAP-TLS, EAP-TTLS, EAP-PEAP	: EAP-TLS, EAP-TTLS, EAP-PEAP	: EAP-TLS, EAP-TTLS, EAP-PEAP	: EAP-TLS, EAP-TTLS, EAP-PEAP
		AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz
Operating Condition	Power Consumption	Max[W/h]	TBD	TBD	TBD	TBD	TBD	TBD
		Typical[W/h]	TBD	TBD	TBD	TBD	TBD	TBD
	Sleep mode		less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W	less than 0.5W
Accessories	Temperature	0°C~ 40°C	0°C~ 40°C	0°C~ 40°C	0°C~ 40°C	0°C~ 40°C	0°C~ 40°C	0°C~ 40°C
		Relative Humidity	10~80%	10~80%	10~80%	10~80%	10~80%	10~80%
	Included	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord	Quick Setup Guide, Warranty Card, Power Cord
		RS232C (In) Gender Remote Controller & Batteries	RS232C (In) Gender Remote Controller & Batteries	RS232C (In) Gender Remote Controller & Batteries	RS232C (In) Gender Remote Controller & Batteries	RS232C (In) Gender Remote Controller & Batteries	RS232C (In) Gender Remote Controller & Batteries	RS232C (In) Gender Remote Controller & Batteries
Optional	Stand	STN-L4355C	STN-L4355C	STN-L4355C	STN-L4355C	STN-L4355C	STN-L4355C	STN-L4355C
	Mount	WMN-B50SC	WMN-B50SC	WMN-B50SC	WMN-B50SC	WMN-B50SC	WMN-B50SC	N/A
Specialty		TBD	TBD	TBD	TBD	TBD	TBD	TBD

* This specification is not a finalized version, so some specifications may change at the end of June.

About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

Smart Signage

For more information about Samsung Smart Signage, visit www.samsung.com/business

Copyright © 2023 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.
416, Maetan 3-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-772, Korea



Crystal UHD Signage
QBC series

Slim design.
Stunning performance.

Introducing the QBC series, the slimmest display in the Samsung’s UHD signage offerings. This products deliver an unparalleled slim design that fits into any business, while delivering the visual quality to make a big impact. The sleek form factor is easily installed to fit any room design and delivers stunning visual performance. Dynamic Crystal Color and Quantum Processor Lite 4K delivering consistent, lifelike colors to any content. This is not just a display for simple advertising. It’s a display that brings the solutions, tools, and picture quality to grow to your business, no matter what industry you’re in.

Key features

Ultra Slim Depth

The unparalleled ultra-slim thickness of 28.5mm makes it the thinnest option in Samsung’s UHD Signage series. It comes with the Slim Fit Wall Mount, which allows you to install it neatly and easily in any environment.

Even Bezels and Centered VESA Holes

The bezels are even on all four sides of the display for a consistent look, while the central VESA mounting holes ensure secure mounting and easy adjustability to portrait mode.

Dynamic Crystal Color

One billion shades of color let you see every subtlety with lifelike color variations. Images are clear and consistent thanks to Samsung’s industry leading video processing and upscaling technology.

Smart Calibration

Guarantee complete brand consistency across every location. Using the Samsung mobile app, calibrate displays to showcase brand logos and other collateral in the exact colors required.

Energy star / EPEAT Bronze

Samsung is making diverse efforts to reduce our environmental impact in smart signage, and encouraging users to pursue a more sustainable life.