

Intimidator Spot 475ZX

- Compact moving head designed for large events
- Onboard USB-C port allows for quick software updates
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- New home position allows for smoother programming
- Dual rotating prisms split the beam for great effects and cover a larger area
- Motorized zoom for short or long throw applications
- ¼-turn hanging bracket allows for single or dual clamp mounting options
- Project crisp gobos from nearly any distance with the motorized focus
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- powerCON®-compatible power input/output connections saves setup time

Specifications

- DMX Channels: 10 or 16
- DMX Connectors: 3 XLR
- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors: 7 + white, split colors, continuous scroll at variable speeds
- Gobos: 7 + open (6 metal + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Gobos: 8 + open, indexing, continuous scroll at variable speeds
- Gobo Size: 25.7 mm outside, 21 mm image, 1.3 mm max thickness
- Prism: 5-facet linear, bi-directional at variable speeds
- Prism: 6-facet round, bi-directional at variable speeds
- Light Source: 1 LED (cool white) 250 W, (10 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Zoom Angle (motorized): 13° to 28°
- Illuminance (13°) : 90,979 lux @ 2 m
- Illuminance (28°) : 24,565 lux @ 2 m
- Illuminance (13°) : 14,557 lux @ 5 m
- Illuminance (28°) : 3,930 lux @ 5 m
- Lumens : 10,710
- Color Temperature: 15,000 K
- Power Linking: 3 units @ 120 V; 7 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 378 W, 3.4 A @ 120 V, 60 Hz
- Power and Current: 372 W, 1.9 A @ 230 V, 50 Hz
- Approvals : CE, UKCA, RoHS, MET



- Weight: 36.2 lb (16.5 kg)
- Size: 14.3 x 10 x 21 in (363 x 250 x 531 mm)
- Optional Controllers: RFC, RFC-XL

