



La Prestige Facet II 34F sublime votre expérience d'écoute avec une nouvelle finition satinée, des renforts optimisés, un filtrage haut de gamme et un câblage en cuivre OFC.

Cette colonne 3 voies, équipée de deux haut-parleurs de grave de 250 mm, deux médiums de 170 mm et d'un tweeter de 25 mm, offre une réponse en fréquence étendue de 25 Hz à 25 kHz, avec une sensibilité élevée de 94 dB.

La charge bass-reflex accordée à 26 Hz assure des basses profondes et maîtrisées, idéales pour la Hi-Fi comme pour le home-cinéma



TECHNIQUE

Type Enceinte colonne - 3 voies - Bass-reflex	Filtre répartiteur- Fc 230 & 4500 Hz - 12dB / 12dB - 12dB / 18dB
Puissance 300 W RMS	Impédance nominale 6 Ω
Amplification recommandée 70 - 350W	Impédance minimale 5,3 Ohms @ 88 Hz
Haut-parleurs Tweeter : 25 mm Médiums : 2 x 170 mm Graves : 2 x 250 mm	Fréquence d'accord bass-reflex 26 Hz
Réponse en fréquence (±3dB) 25Hz - 25kHz	Bornier Argentés pour bi-câblage ou bi-amplification
Sensibilité 94dB / 1W / 1m	

DIMENSIONS
POIDS

Dimensions sans/avec pieds L295 x H1190 / L1230 x P376 mm	Poids sans/avec pieds 43,3 kg / 44 kg
Espace d'encombrement L371 x P436 mm	

PACKAGING

Packaging dimensions L1345 x H475 x P540 mm	Poids brut 51 kg
---	----------------------------

FINITIONS
-
CODES
PRODUITS

	Finition Noir mat	SKU ELIPF234FMBK	EAN 3700795194584
	Finition Blanc mat	SKU ELIPF234FMWT	EAN 3700795194591
	Finitions Noir mat - Noyer	SKU ELIPF234FWNBK	EAN 3700795194607

elipson® | Prestige Facet II 34F

FLOORSTANDING LOUDSPEAKER - 3 WAY - BASS-REFLEX



The Prestige Facet II 34F enhances your listening experience with a new satin finish, optimised bracing, high-end filtering and OFC copper cabling.

This 3-way floorstanding loudspeaker, equipped with two 10" bass drivers, two 7" midrange drivers and a 1" tweeter, offers an extended frequency response from 25 Hz to 25 kHz, with a high sensitivity of 94 dB.

The bass-reflex load tuned to 26 Hz ensures deep, controlled bass, ideal for both Hi-Fi and home cinema.





TECHNICAL

Type Floorstanding loudspeaker 3 way - Bass-reflex	Crossover 230 & 4500 Hz - 12dB / 12dB - 12dB / 18dB
Power 300 W RMS	Nominal impedance 6 Ω
Power amplifier 70 - 350W	Minimum Impedance 5,3 Ohms @ 88 Hz
Drive-Units Tweeter : 1" Mid-ranges : 2 x 7" Woofers : 2 x 10"	Tuned bass-reflex frequency 26 Hz
Frequency response (±3dB) 25Hz - 25kHz	Terminals Silver plated for bi-wiring or bi-amplification
Sensitivity 94dB / 1W / 1m	

DIMENSIONS
WEIGHTS

Dimensions without/with feet W295 x H1190 / W1230 x D376 mm	Weight without/with feet 43,3 kg / 44 kg
Space requirements W371 x D436 mm	

PACKAGING

Packaging dimensions W1345 x H475x D540 mm	Gross weight 51 kg
--	------------------------------

FINISHES
-
PRODUCTS
CODES

	Finish Black matt	SKU ELIPF234FMBK	EAN 3700795194584
	Finish White matt	SKU ELIPF234FMWT	EAN 3700795194591
	Finishes Black matt - Walnut	SKU ELIPF234FWNBK	EAN 3700795194607