

SPEAKER IC SERIES

IC120

SONORA
PROFESSIONAL
SERVICES INTÉGRATION
AUDIOVISUELLE

► Technical Data

Impedance
Frequency Range
System
Broadband Driver
Rated Driver
Maximum Power
Crossover Point

4Ω
-6 db 120 Hz – 20 kHz
Line array speaker
4 x (20 x 120 mm)
40 W
80 W
Passive: BEC Crossover
Active: Bessel 6 db, 180 hz

► Radiation

Radiation angle, Horiz.
Radiation angle, Vert.
Sensitivity
Max. Rated SPL

180°
40°
88 dB / W / 1 m
106 dB / W / 1 m


► Housing

Material
Color

Number of Drivers
Mounting (included)
Mounting (optional)

Operating Temp.
Dimensions
Weight
Input Connectors

Aluminium
Black, White, Silver, Gold
special on request
4
Metal Angle Bracket
Ceiling Mount,
In-Wall Mounting,
Magnetic On-Wall Bracket,
Stacking Adapter
0 – 100° C
37,5 x 1206 x 23 mm
1.2 kg
Phoenix 2-pole,
RM: 5,08 mm



IC120 Black – 4262477791607
IC120 White – 4262477791591
IC120 Silver – 4262477791515
IC120 Gold – 4262477791522