

Its best feature: unmatched versatility

A 4K UHD digital whiteboard that adds versatility to healthcare

The Samsung WMB series digital whiteboard can enhance your level of care in so many areas. It's ideal for multimedia presentations and collaborative meetings, whether in-person or remote. Add the rolling stand (55" WMB) and it's a mobile signage board, a children's art palette or a senior living residence dance instructor. The WMB series can be whatever you, your staff, your visitors or your patients need it to be.



Improve care in so many ways

Annotate and collaborate in real time

Make every conference room and huddle room an interactive meeting space. With Cisco Webex, team members can collaborate either in person or remotely.



Add the optional rolling stand to the 55" WMB, and you have a signage solution for a pop-up COVID testing site or immunization clinic. You can display pre-check in directions, a reminder to wear a mask and more.



Let patients or residents create artwork, then print or email them to family and friends. Host an impromptu movie matinee. Allow family and friends to visit virtually. Set up a virtual fitness instructor for your residents. And so much more.







				1916***
iamsung Interactive Displays	WM55B	WM65B	WM75B	WM85B
K UHD Resolution	✓	✓	✓	✓
	✓	✓	✓	✓
Shatter-Resistant Screen ¹	✓	✓	✓	✓
Antimicrobial-Coated Screen ²	✓	✓	✓	✓
Palm Erase	✓	✓	✓	✓
Brush Mode	✓	✓	✓	✓
Cisco Certified	✓	✓	✓	✓
Miracast	✓	✓	✓	✓
ogitech Compatible	✓	✓	✓	✓
Multi-Device Mirroring			✓	✓
Airplay	✓	✓	✓	✓
RMS (Remote Management System)	✓	✓	✓	✓
)PS			✓	✓
Havrion Emergency Response			✓	✓
Varranty	3 years (2 years extended option available)	3 years (2 years extended option available)	5 years	5 years

Full-featured flexibility



Responsive and intuitive touch

Exceptionally responsive touch displays enable staff members and patients to write and draw smoothly and naturally. Flexible erasing requires just a swipe of a finger or palm. And multi-touch allows multiple users to simultaneously write or draw on the display for enhanced collaboration.



Best-in-class annotation

Take notes. Highlight critical details. Your team can annotate onto photos, documents, web browsers and applications, then save and share.



Antimicrobial coating and shatterresistant glass

The screen surface of the WMB series is treated with an antimicrobial coating,¹ while shatter-resistant glass helps reduce hazards.²



Multiple virtual conferencing options

The WMB series offers multiple ways to host meetings, allows virtual visiting between patients or residents and family, and more. Access Cisco WebEx® with a simple tap on the display's screen. And with Logitech device compatibility, you can easily use your Zoom and Teams apps.³



Start meetings faster with USB-C

Users can simply connect their device to the USB-C port to start sharing content without any hassle. In addition to fast data, audio, video transfer and touch control, USB-C also provides 65W external device charging.



Multi-device casting for enhanced collaboration

With SmartView+ you can mirror up to four devices to the display simultaneously, regardless of OS³: Android, Chrome, iOS or Windows. Bidirectional communication allows you to the display's content from any connected device, as well as annotate a device's content right on the display.



Connect with Airplay 2

Effortlessly share or mirror almost anything from your iOS device or Mac directly to the WMB Interactive Display.³



Manage from anywhere, update on the fly

Centrally manage your interactive displays, update firmware and send out notifications with MagicINFO Remote Management solution.⁴



Emergency alerts

Use MagicINFO to create emergency notifications, such as evacuation instructions customized to each display location. Havrion Protect³ software integrates with your existing emergency monitoring systems to automatically broadcast your messages in an emergency.



Up to 5-year warranty

A 5-year parts and labor warranty on the 75" and 85" models, and a 3-year warranty on the 55" and 65" models with the option to extend it an additional two years, leaves you free to worry about more important things.





Accessories



Rolling Stand

55"

STN-WM55R

Have impromptu meetings anywhere. Turn any area into an entertainment area for kids or seniors. Set up mobile digital signage where you need it.



Connectivity Tray

55" and 65" CY-TF65BR

Easily add multiple connections for increased versatility.



OPS Box

75", 85" CY-PBRK200

An OPS box lets you use third-party apps and tools.



Wall Mounts

55": WMN-4277SF

65": WMN-WM65R

75": WMN6575SF

85": WMN8200SF

A wall mount can save space and give a cleaner overall appearance.



CY-PENR

Two pens are included with each WMB display. For even greater collaboration, have additional pens on hand.

Connectivity

- 1. Optional Tray
- Service
 HDMI1
- DisplayPort
- 6. Touch Out
- 7. Audio Out
- OPS SLOT

Front

2. LAN



Back



Connectivity Tray (CY-TF65BBC)

USB In (External)

9. USB

- 11. USB Out (External)
- 12. Touch Out 2

- 13. HDMI 2
- 14. USB-C (without P/D)



			WM55B	WM65B	WM75B	WM85B
	Diagonal Size		55"	65"	75"	85"
	Type		New Edge, 60Hz	New Edge, 60Hz	New Edge, 60Hz	New Edge, 60Hz
	Resolution		3,840 x 2,160 (Landscape)	3,840 x 2,160 (Landscape)	3,840 x 2,160 (Landscape)	3,840 x 2,160 (Landscape)
nel	Brightness (Typ.)		350 nits (without glass)	350 nits (without glass)	350 nits (without glass)	350 nits (without glass)
	Contrast Ratio (Typ.)		4000:1 (Typ.) (without glass)	4000:1 (Typ.) (without glass)	4700:1 (Typ.) (without glass)	4700:1 (Typ.) (without glass)
	Viewing Angle (H/V)		178° (H) / 178° (V)	4000:1 (Typ.) (without glass) 178° (H) /178° (V)	4700:1 (Typ.) (without glass) 178° (H) /178° (V)	4700:1 (Typ.) (without glass) 178° (H) / 178° (V)
	Viewing Angle (H/V) Response Time (G-to-	C)	8ms (Typ.)	9mc (Tun)	1/0 (II) / 1/0 (V)	1/0 (П)/ 1/0 (V)
eration Hours	Response fille (G-to-	<u>u)</u>	16/7	8ms (Typ.)	6ms (Typ.)	6ms (Typ.)
	I Company		10//	10//		
ound Spe	SpeakerType	Lvc.t.	Built in Speaker (10W x 2) (Basic) HDMI1, DP1 (With Tray) HDMI1, USB-C	Built in Speaker (10W x 2) (Basic) HDMI1, DP1 (With Tray) HDMI1, USB-C	Built in Speaker (10W x 4) HDMI 2 (Rear1, Front 1), DP1, USB C (Front), OPS I/F	Built in Speaker (10W x 4) HDMI 2 (Rear1, Front 1), DP1, USB C (Front), OPS I/F
	Input	Video	(Basic) HDMLI, DPT (WILLI ITay) HDMLI, USB-C	(Basic) HDMI I, DPT (WILLI Tray) HDMI I, USB-C		
		USB	(Basic) USB 1 (With Tray) USB 2, USB External (In / Out) 1	(Basic) USB 1 (With Tray) USB 2, USB External (In / Out) 1	2 (For SoC, Rear / Front), 1 (for external 3.0x1 (Front))	2 (For SoC, Rear / Front), 1 (for external 3.0x1 (Front))
		Audio	1 (Stereo Mini Jack)	1 (Stereo Mini Jack)	1 (Stereo Mini Jack)	1 (Stereo Mini Jack)
nnectivity	Output	Touch Out	(Basic) Touch Out 1 (USB Upstream Type)	(Basic) Touch Out 1 (USB Upstream Type)	Touch Out 2 (USB Upstream Type, Front 1, Rear1)	Touch Out 2 (USB Upstream Type, Front 1, Rear 1)
			(With Tray) Touch Out 1	(With Tray) Touch Out 1		
	External	Control	Touch Input, RS232C thru Stereo Jack, RJ45 (For MDC)	Touch Input, RS232C thru Stereo Jack, RJ45 (For MDC)	Touch Input, RS232C thru Stereo Jack, RJ45 (For MDC)	Touch Input, RS232C thru Stereo Jack, RJ45 (For MDC)
	Bluetooth / Wi-Fi		Yes (Keyboard / Mouse, Speaker)	Yes (Keyboard / Mouse, Speaker)	Yes (Keyboard / Mouse, Speaker)	Yes (Keyboard / Mouse, Speaker)
	Type		IR .	IR .	IR .	IR .
	Number of Drawing		Multi-Annotation up to 4	Multi-Annotation up to 4	Multi-Annotation up to 4	Multi-Annotation up to 4
	Touch Pen Type		Passive Pen with Magnet	Passive Pen with Magnet	Passive Pen with Magnet	Passive Pen with Magnet
			2mm / 4mm / 8mm / 50mm	2mm / 4mm / 8mm / 50mm	2mm / 4mm / 8mm / 50mm	2mm / 4mm / 8mm / 50mm
	Object Recognition R	ange				
			(Brush Mode: Dynamic Object Recognition)	(Brush Mode: Dynamic Object Recognition)	(Brush Mode: Dynamic Object Recognition)	(Brush Mode: Dynamic Object Recognition)
	Touch Response Time		6.7ms	6.7ms	6.7ms	6.7ms
	Drawing Speed (Touch	rtatency)	26ms	26ms	26ms	26ms
	Haze		8%~12%	8%~12%	8%~12%	8%~12%
	Thickness		2.85T	3.2T	3.2T	3.2T
	Hardness		Heat Semi-Strengthened Glass	Heat Semi-Strengthened Glass	Heat Semi-Strengthened Glass	Heat Semi-Strengthened Glass
	Additional Film		AG Film (Anti glare), Hydrophobic Coated PET (Shatter-proof Film), Antimicrobial Coating	AG Film (Anti glare), Hydrophobic Coated PET (Shatter-proof Film), Antimicrobial Coating	AG Film (Anti glare), Hydrophobic Coated PET (Shatter-proof Film), Antimicrobial Coating	AG Film (Anti glare), Hydrophobic Coated PET (Shatter-proof Film), Antimicrobial Coating
	Additional Film		(Shatter-proof Film), Antimicrobial Coating	(Shatter-proof Film), Antimicrobial Coating	(Shatter-proof Film), Antimicrobial Coating	(Shatter-proof Film), Antimicrobial Coating
	Туре		Internal	Internal	Internal (Main 1ea, OPS 1ea)	Internal (Main 1ea, OPS 1ea)
	Power Supply		AC100-240V 50/60Hz	AC100-240V 50/60Hz	AC100-240V 50/60Hz	AC100-240V 50/60Hz
	. оне: зарра	Max (W/h)	154W (100-240V)	192.5W (100-240V)	473W (100-240V), 451W(220-240V), OPS (16V/4.5A)	528W (100-240V), 506W (220-240V), OPS (16V/4.5A)
or		Typical (W/h)	95W	124W	187W	197W
er	Power Consumption	Rating (W/h)	140W		430W (100-240V), 410W (220-240V), OPS (16V/4.5A)	480W (100-240V), 460W (220-240V), OPS (16V/4.5A)
	Consumption			175W		
		Stand-by (W/h)	0.5	0.5	0.5	0.5
		BTU (W/h)	525.14W	656.425W	1612.93W (100-240V), 1537.91W (220-240V), OPS (16V/4.5A)	1800.48W (100-240V), 1725.46W (220-240V), OPS (16V/4.5A)
	Dimensions	Set	1297.4mm x 768.2mm x 59.9mm/ 51.16" x 30.24" x 2.36"	1522.4mm x 897.6mm x 62.9mm / 59.94" x 35.34" x 2.48"	1724mm x 1026.3mm x 89mm / 67.87" x 40.41" x 3.5"	1945.8mm x 1151.1mm x 89mm / 76.61" x 45.32" x 3.5"
	Diffictions	Package	1464mm x 915mm x 190mm / 57.64" x 36.02" x 7.48"	1691mm x 1055mm x 198mm / 66.57" x 41.54" x 7.8"	1905mm x 1189mm x 287mm / 75" x 46.81" x 11.3"	2136mm x 1318mm x 260mm / 84.09" x 51.89" x 10.24"
	Weight	Set	28.6 kg / 63.1 lbs.	39.7 kg / 87.5 lbs.	59.3 kg / 130.7 lbs.	75.2 kg / 165.8 lbs.
	weight	Package	35.9 kg / 79.1 lbs.	48.2 kg / 106.3 lbs.	72.2 kg / 159.2 lbs.	91.6 kg / 201.9 lbs.
	Color		Grav White	Gray White	Grav White	Gray White
chanical	VESA Mount		400 x 400	400 x 400	400 x 400	600 x 400
	Protection Glass		Yes	Yes	Yes	Yes
	Stand Type (Optional)		Stand / Wall Mount (STN-WM55R / WMN4277SF)	Wall Mount (WMN-WM65R)	Wall Mount (WMN6575SE)	Wall Mount (WMN8200SFXZA)
	Media Player Option T	irno	N/A	N/A	OPS Slot Support	OPS Slot Support
	Detation	уре	Landscape / Portrait	Landscape / Portrait	Landscape only	Landscape only
	Power Cable Length		3M / 2.4M	3M / 2.4M	3M /2.4M	3M /2.4M
			0°C~ 40°C / 32°F~104°F	0°C~ 40°C / 32°F ~ 104°F	0°C~ 40°C / 32°F~104°F	0°C~40°C / 32°F~104°F
eration	Operating Temperatur	re			0°C~ 40°C / 32 F~ 104 F	U-C-40-C/32 F-104 F
	Humidity		10~80%, Non-condensing	10~80%, Non-condensing	10-80%, non-condensing	10~80%, non-condensing
	Key		Flip App	Flip App	Flip App	Flip App
	Orientation		Landscape / Portrait	Landscape / Portrait	Landscape	Landscape
	Hardware		Touch module (IR), Built in Speaker (20W 2CH), WiFi / BT Module	Touch module (IR), Built in Speaker (20W 2CH), WiFi / BT Module	Touch Overlay (IR), Front Connectivity, OPS I/F Support (w/OPS Box), Built in Speaker (40W 4CH), WiFi / BT Module Embedded	Touch Overlay (IR), Front Connectivity, OPS I/F Support (w/OPS Built in Speaker (40W 4CH), WiFi / BT Module Embedded
	Haluwale		Embedded	Embedded	Built in Speaker (40W 4CH), WiFi / BT Module Embedded	Built in Speaker (40W 4CH), WiFi / BT Module Embedded
		First screen	Flip S/W (Whiteboarding App)	Flip S/W (Whiteboarding App)	Flip S/W (Whiteboarding App)	Flip S/W (Whiteboarding App)
			3 111	2 11	3 111	3 111
		Apps	Document Viewer, Smartview+, Video Player, Web Browser,	Document Viewer, Smartview+, Video Player, Web Browser,	Document Viewer, Smartview+, Video Player, Web Browser, Workspace, (RDP /VNC, Office365, VMWare)	Document Viewer, Smartview+, Video Player, Web Browser, Workspace, (RDP /VNC, Office365, VMWare),
			Workspace, (RDP /VNC, Office365, VMWare)	Workspace, (RDP /VNC, Office365, VMWare)	workspace, (KDP / VNC, Office365, VMWare)	workspace, (RDP / VNC, Office365, VMWare),
	Software	WebRTC	Yes	Yes	Yes	Yes
		Ungradable web engine	Yes	Yes	Yes	Yes
		Upgradable web engine Smartview+ Airplay	Yes	Yes	Yes	Yes
		Airplay	Yes	Yes	Yes	Yes
		Platform	Pontus-M (Tizen 6.5)	Pontus-M (Tizen 6.5)	Pontus-M (Tizen 6.5)	Pontus-M (Tizen 6.5)
	Internal Discour	Practicitii	CA72 Our J (17CHz)	CA72 O (17CH-)	Control A7217CH - Overal Cons CDU 2MD L2	Control A72.1.7 Clar Overal Const Chill 2MD L2
	Internal Player (Embedded H/W)	Processor	CA72 Quad (1.7GHz)	CA72 Quad (1.7GHz)	Cortex A72 1.7GHz Quad-Core CPU 2MB L2	Cortex A72 1.7GHz Quad-Core CPU 2MB L2
	(Embedded H/W)	Storage	32GB (2.65GB Occupied by O/S, 29.35GB Available)	32GB (2.65GB Occupied by O/S, 29.35GB Available)	32GB (2.65GB Occupied by O/S, 29.35GB Available)	32GB (2.65GB Occupied by O/S, 29.35GB Available)
		Operating System	Tizen ó.5: Samsung Proprietary OS (VDLinux) 802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	Tizen 6.5: Samsung Proprietary OS (VDLinux) 802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	Tizen 6.5: Samsung Proprietary OS (VDLinux) 802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	Tizen 6.5: Samsung Proprietary OS (VDLinux) 802.1x (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP
rity			8U2.Ix (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	8UZ.1x (WPAZ Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	8UZ.Ix (WPAZ Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP	8U2.Ix (WPA2 Enterprise): EAP-TLS, EAP-TTLS, EAP-PEAP
	Included		Power Cord, USB Upstream Cable (1 ea), Pen (2 ea, Black),	Power Cord, USB Upstream Cable (1 ea), Pen (2 ea, Black),	Power Cord, USB Upstream Cable (1 ea), Pen (2 ea, Black),	Power Cord, USB Upstream Cable (1 ea), Pen (2 ea, Black),
	mctudeu		Warranty / Quick Start Guide	Warranty / Quick Start Guide	Warranty / Quick Start Guide	Warranty / Quick Start Guide
		Stand	STN-WM55R	N/A (3rd party stand can be supported through VESA)	N/A (3rd party stand can be supported through VESA)	N/A (3rd party stand can be supported through VESA)
ssories		Mount	WMN-4277SF	WMN-WM65R	WMN6575SE	WMN8200SFXZA
recessories	Optional	OPS Mount		-	CY-PBRK200	CY-PBRK200
	Sptionat	Tray	CY-TF65BR	CY-TF65BR		C. I DIMEGO
		Flip Pen	CY-PFNR CY-PFNR	CY-PFNR	CY-PENR	CY-PENR
		гарген	3 Years (Optional 2 Years Extended Warranty Available)	3 Years (Optional 2 Years Extended Warranty Available)	5 Years	5 Years
				1.5 Years (Upupital / Years Extended Warranty Available)	10 Teals	10 Yedis

SAMSUNG

©2023 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. All other brand, product, service names and logos are trademarks of their respective manufacturers and companies. Screen images simulated. Non-metric weights and measurements are approximate. Specifications and designs are subject to change without notice. See samsung.com for detailed information. Printed in USA. DIGSIG-HC-WMB-DSHT-MAR23T

'Antimicrobial coating does not protect users or other items against bacteria, viruses including Covid-19, germs, and other disease organisms. Antimicrobial coating on surface of screen only. 'A shatter-resistant film is applied to the screen to help mitigate the hazards of shattering glass, but it does not protect the screen from physical impact. 'This feature requires a no-cost firmware upgrade. 'Requires MagicINFO license.