

ClickShare CX-20

Transform small meeting rooms and huddle spaces into inspiring conference facilities.



- Full BYOD support
- Remote collaboration
- Triple agnostic: works with any device, and UC technology and any brand of AV peripheral
- Enhanced security
- Connected and cloud managed
- Delivered with 1 Conferencing Button
- Collaborate with Conferencing Button or Collaboration App

The modern world of enterprise requires smooth collaboration and flexibility, especially when it comes to team meetings in huddle rooms, and this is exactly what Barco ClickShare CX-20 provides. Encouraging creative innovation through seamless wireless conferencing, ClickShare CX-20 can make meetings more inspiring and more productive.

Announced now, available soon
Start a huddle meeting from your device
Decide how you want to collaborate
Enhanced security and seamless integration

PRODUCT SPECIFICATIONS**CLICKSHARE CX-20**

Dimensions de la Base Unit ClickShare	
Dimensions (H x l x P)	34 mm x 135 mm x 135 mm
Alimentation	Standard 110/220 V AC plug
Consommation	Operational: 5-10W, 24W Max
Poids	900 gr
Spécifications générales	
Systèmes d'exploitation	Windows 8/8.1/10, macOS 10.13 and higher. Android v9 and higher (ClickShare app). iOS 12 and higher (ClickShare app)
Sorties vidéo	4K UHD (3840*2160) @ 30Hz, HDMI 1.4b
Sortie audio	USB, HDMI
USB	1 X USB-A, 1 X USB-C
Clickshare Buttons	1
ClickShare App	Desktop & Mobile
Native protocols	Aiplay, Google Cast, Miracast*
Niveau sonore	Max. 25dBA @ 0-30°C Max. 30dBA @ 30-40°C
Protocole d'authentification	WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode
Protocole de transmission sans fil	IEEE 802.11 a/g/n/ac and IEEE 802.15.1
Portée	Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band 2.4 GHz and 5 GHz (DFS)
Bande de fréquence	2.4 GHz and 5 GHz (DFS channels supported in select number of countries)
Connexions	1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front)
Plage de température	Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F)
Humidité	Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing
Système antivol	Kensington lock
Certifications	FCC/CE
Touch screen support & Interactivity	/
Room Dock (peripheral support)	Yes
Local view & moderation	Local view of the room display only
Connexion réseau	LAN & WiFi *
Management and reporting	Yes
Garantie	1 year standard, 5 years coverage via SmartCare
*	* depends on configuration, available in future firmware updates



Last updated: 27 Jan 2020

Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.